2.4GHz 4W 36dBm WiFi Signal Booster

SKU: 0305SH200767

Model: SH24Gi4000P

P/N: 24Gi4000014

Barcode: 6958917600834

Features:

2.4GHz, Max. 4000mW output power; Aluminum-alloy case by CNC, anti-interference; Small size, Safe & Power saving; Full kit, easy to install; For house, office, IP cameras, supermarkets....

Technical Specifications:

Booster Model: SH24Gi4000

Operating range : 2400~2500MHz Channel width: 20Mhz&40Mhz Supported standards: IEEE 802.11b/a/g/n Operation mode: Bi-directional, half-duplex, time division duplex Connector type: To radio SMA female (hole inside). To antenna RP-SMA female (pin inside) Output power: 4000mW (36dBm) Input power: 0 ~ 20dBm Transmit gain: 17 – 20dB Receiver gain: ≤12dB Noise figure: ≤3.5dB typical Frequency response: ±1dB over operating range Power adapter: 6V/2A DC, 100~240V Operating temperature: -20°C to +70°C Operating humidity: Up to 75% relative humidity Material: Cast aluminum LED light: Power status / activity status LED Booster weight: 133g Booster size: 9.7 x 6.4 x 1.7cm

Package weight: 550g Package size: 19.5 x 16.1 x 7cm

Package contents:

1 x SH24Gi4000 WiFi booster 1 x RG316 cable with SMA connectors (20cm) 1 x 6dBi omni antenna 1 x power supply

